



# SAFETY DATA SHEET

## SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

**Product ID:** 1646  
**Product Name:** AlbaChem Antistatic Spray  
**Revision Date:** May 23, 2023 **Date Printed:** 1.0 May 23, 2023  
**Version:** **Supersedes Date:** Feb. 12, 2020  
**Manufacturer's Name:** ALBATROSS  
**Address:** P.O.BOX 6446 LONG ISLAND, NY. 11106 , US  
**Emergency Phone:** CHEMTREC US : 1-800-424-9300, INTERNATIONAL CALLS : 1-703-527-3887 MEXICO: 01-800-681-9531  
**Information Phone Number:** 718-392-6272  
**Fax:**  
**Product/Recommended Uses:** Static Control

## SECTION 2) HAZARDS IDENTIFICATION

### Classification

Aerosols Category 1  
Eye Irritation - Category 2A  
Skin Irritation - Category 3

### Pictograms



### Signal Word

Danger

### Hazardous Statements - Physical

H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.

### Hazardous Statements - Health

H319 - Causes serious eye irritation.  
H316 - Causes mild skin irritation.

### Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P103 - Read label before use.

### Precautionary Statements - Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

### Precautionary Statements - Response

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

### Precautionary Statements - Storage

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### Precautionary Statements - Disposal

No precautionary statement available.

### Hazards Not Otherwise Classified (HNOC)

None.

## SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0007732-18-5	WATER	31% - 51%
0000064-17-5	ETHYL ALCOHOL	25% - 40%
0068476-86-8	Petroleum gases, liquefied, sweetened	14% - 23%
0000532-32-1	SODIUM BENZOATE	0.0% - 0.2%
0068391-01-5	Alkyl dimethyl benzyl ammonium chloride	Trace
0000103-95-7	Benzenepropanal, .alpha.-methyl-4-(1-methylethyl)-	Trace
0000060-12-8	BENZEETHANOL	Trace
0000140-11-4	BENZYL ACETATE	Trace
0000080-54-6	Benzenepropanal, 4-(1,1-dimethylethyl)-.alpha.-methyl-	Trace

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

## SECTION 4) FIRST-AID MEASURES

### Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing.

If exposed/If you feel unwell/If concerned: Call a POISON CENTER/doctor.

Eliminate all ignition sources if safe to do so.

### Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before re-use.

IF exposed or concerned: Get medical advice/attention.

### Eye Contact

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

### Ingestion

Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position.

### Most Important Symptoms and Effects, Acute or Delayed

No data available.

### Immediate Medical Attention and Special Treatment, if necessary

No data available.

## SECTION 5) FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Dry chemical, foam, carbon dioxide. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only.

Do not direct a solid stream of water or foam into hot, burning pools this may result in frothing and increase fire intensity.

### Unsuitable Extinguishing Media

No data available.

### Specific Hazards in Case of Fire

Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Product is highly flammable and forms explosive mixtures with air, oxygen, and all oxidizing agents. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back.

During a fire, irritating and highly toxic gases may be generated during combustion or decomposition. High temperatures can cause sealed containers to rupture due to a build up of internal pressures. Cool with water.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

Container could potentially burst or be punctured upon mechanical impact, releasing flammable vapors.

### Fire-Fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

### Special Protective Actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## SECTION 6) ACCIDENTAL RELEASE MEASURES

### Emergency Procedure

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Do not touch or walk through spilled material.

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

### Recommended Equipment

Wear liquid tight chemical protective clothing in combination with positive pressure self-contained breathing apparatus (SCBA).

### Personal Precautions

Avoid breathing vapor. Avoid contact with skin, eye or clothing. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

### Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

### Methods and Materials for Containment and Cleaning Up

Absorb liquids in vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal.

## SECTION 7) HANDLING AND STORAGE

### General

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.  
 Use good personal hygiene practices.  
 Eating, drinking and smoking in work areas is prohibited.  
 Remove contaminated clothing and protective equipment before entering eating areas.  
 Eyewash stations and showers should be available in areas where this material is used and stored.

### Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

### Storage Room Requirements

Do not cut, drill, grind, weld or perform similar operations on or near containers. Do not pressurize containers to empty them.  
 Store at temperatures below 120°F.

## SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

### Eye Protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

### Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

### Respiratory Protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

### Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)
BENZYL ACETATE								
DIETHYL PHTHALATE								
ETHYL ALCOHOL	1000	1900			1			1000
Petroleum gases, liquefied, sweetened	500	2000			1			

Chemical Name	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)
BENZYL ACETATE					10			
DIETHYL PHTHALATE	5					5		
ETHYL ALCOHOL	1900						1000	
Petroleum gases, liquefied, sweetened								

## SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

### Physical and Chemical Properties

Density VOC Less H2O and Exempts	5.68738 lb/gal
VOC Actual(g/l)	436.98200 g/l
VOC Regulatory(g/l)	436.98200 g/l
VOC Regulatory(lb/gal)	3.64669 lb/gal
Density	6.64001 lb/gal
Density VOC	3.64669 lb/gal
% VOC	54.91990%

---

Appearance	Clear mist spray
Odor Threshold	N.A.
Odor Description	Characteristic
pH	N.A.
Flammability	N/A
Water Solubility	N.A.
Flash Point Symbol	N.A.
Flash Point	N.A.
Viscosity	N.A.
Lower Explosion Level	N.A.
Upper Explosion Level	N.A.
Vapor Pressure	N.A.
Vapor Density	N.A.
Freezing Point	N.A.
Melting Point	N.A.
Low Boiling Point	N.A.
High Boiling Point	N.A.
Auto Ignition Temp	N.A.
Evaporation Rate	N.A.
VOC Composite Partial Pressure	N.A.

## SECTION 10) STABILITY AND REACTIVITY

### Stability

Stable under normal storage and handling conditions.

### Hazardous Reactions/Polymerization

Will not occur.

### Conditions to Avoid

Avoid heat, sparks, flame, high temperature and contact with incompatible materials.  
Dropping containers may cause bursting.

### Incompatible Materials

Avoid strong oxidizers, reducers, acids, and alkalis.

### Hazardous Decomposition Products

No data available.

## SECTION 11) TOXICOLOGICAL INFORMATION

### Likely Route of Exposure

Inhalation, ingestion, skin absorption.

### Skin Corrosion/Irritation

Prolonged or repeated contact with this product may dry and/or defat the skin. This product may be harmful if it is absorbed through the skin.

Causes mild skin irritation.

0000064-17-5 ETHYL ALCOHOL

Contact can irritate the skin. Prolonged or repeated exposure can cause drying and cracking of the skin with peeling, redness and itching.

0000084-66-2 DIETHYL PHTHALATE

Can irritate the skin.

### Serious Eye Damage/Irritation

Eye contact may lead to permanent damage if not treated promptly.

Liquid or vapors may irritate the eyes.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Eye contact may lead to permanent damage if not treated promptly.

Causes serious eye irritation.

0000084-66-2 DIETHYL PHTHALATE

Can irritate the eyes.

### Respiratory/Skin Sensitization

No data available.

### Germ Cell Mutagenicity

No data available.

### Carcinogenicity

No data available.

### Reproductive Toxicity

0000064-17-5 ETHYL ALCOHOL

High concentration may damage the fetus.

### Specific Target Organ Toxicity - Single Exposure

0000064-17-5 ETHYL ALCOHOL

Exposure can cause headache, drowsiness, nausea and vomiting, and unconsciousness. It can also affect concentration and vision.

0000084-66-2 DIETHYL PHTHALATE

May cause headache, dizziness, and nausea. Inhalation may irritate the nose and throat and result in coughing and wheezing.

### Specific Target Organ Toxicity - Repeated Exposure

Causes damage to organs through prolonged or repeated exposure.

0000064-17-5 ETHYL ALCOHOL

Repeated high exposure may affect the liver and the nervous system. Chronic ingestion of ethanol may cause liver cirrhosis.

0000084-66-2 DIETHYL PHTHALATE

May damage the nervous system.

### Aspiration Hazard

No data available.

### Acute Toxicity

If inhaled, may cause dizziness, nausea, upper respiratory irritation, drowsiness, mental depression or narcosis, difficulty in breathing, irregular heart beats.

0000064-17-5 ETHYL ALCOHOL

Inhalation can irritate the nose, throat and lungs.

### Potential Health Effects - Miscellaneous

0000064-17-5 ETHYL ALCOHOL

The following medical conditions may be aggravated by exposure: liver disease. Tests in some laboratory animals indicate this compound may have embryotoxic activity. Tests in animals demonstrate reproductive toxicity. Ingestion may cause any of the following: stupor

(central nervous system depression), gastrointestinal irritation. If absorbed through the skin, may be: harmful.

### Likely Routes of Exposure

0000064-17-5 ETHYL ALCOHOL

The substance can be absorbed into the body by inhalation of its vapor or by ingestion.

0000084-66-2 DIETHYL PHTHALATE

Ingestion, inhalation, and through the skin.

0000064-17-5 ETHYL ALCOHOL

LC50 (mouse): Approximately 21000 ppm (4-hour exposure); cited as 39 g/m3 (4-hour exposure) (1, unconfirmed)

LD50 (oral, rat): 7060 mg/kg (41); 10600 mg/kg (41); 13660 mg/kg (37)

LD50 (oral, mouse): 3450 mg/kg (1, unconfirmed)

LD50 (oral, guinea pig): 5560 mg/kg (37)

0000140-11-4 BENZYL ACETATE

LD50 (oral, rat): 2.49 g/kg(7)

LD50 (oral, mouse): 830 mg/kg (8, unverifiable; translation of original not available)

LD50 (oral, guinea pig): 2.2 g/kg (8, unverifiable; translation of original not available)

LD50 (oral, rabbit): 2.6 g/kg (6)

LD50 (dermal, rabbit): Greater than 5 g/kg(7)

## SECTION 12) ECOLOGICAL INFORMATION

### Toxicity

0000064-17-5 ETHYL ALCOHOL

S gairdneri: 13.0g/l (96hr LC50) Nauplii : 858 g/l (48hr EC50) Ceriodaphnia dubia : 9.6mg/l (10 day NOEC) Freshwater Fish 250mg/l (NOEC) Reference: REACH registration Dossier.

### Persistence and Degradability

0000064-17-5 ETHYL ALCOHOL

Readily biodegradable. Half-life in air = 38 h

0000084-66-2 DIETHYL PHTHALATE

Readily biodegradeable.

### Bio-accumulative Potential

0000064-17-5 ETHYL ALCOHOL

Substance has a low potential for bioaccumulation (log Kow3),

0000084-66-2 DIETHYL PHTHALATE

Potential for bioaccumulation is low.

### Mobility in Soil

No data available.

### Other Adverse Effects

No data available.

### Results of the PBT and vPvB assessment

0000084-66-2 DIETHYL PHTHALATE

Not a PBT/vPvB substance.

## SECTION 13) DISPOSAL CONSIDERATIONS

### Waste Disposal

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

**SECTION 14) TRANSPORT INFORMATION**

**U.S. DOT Information**

Ground Transportation: (Continental United States, Canada & Mexico): Limited Quantity

**IMDG Information**

Shipping Name: Aerosols  
 UN/NA #: 1950  
 Hazard Class: 2.1  
 Required Placard: Limited Quantity  
 Marine Pollutant: No data available

**IATA Information**

Shipping Name: Aerosols,  
 UN/NA #: 1950  
 Hazard Class: 2.1

**SECTION 15) REGULATORY INFORMATION**

CAS	Chemical Name	% By Weight	Regulation List
0007732-18-5	WATER	31% - 51%	DSL,TSCA
0000064-17-5	ETHYL ALCOHOL	25% - 40%	Canada_NPRI,DSL,SARA312,VOC,TSCA
0068476-86-8	Petroleum gases, liquefied, sweetened	14% - 23%	DSL,SARA312,VOC,TSCA
0063148-62-9	SILICONE	0.0% - 0.4%	DSL,SARA312,VOC_exempt,TSCA
0000120-51-4	BENZYL BENZOATE	0.0% - 0.3%	DSL,SARA312,VOC,TSCA
0000532-32-1	SODIUM BENZOATE	0.0% - 0.2%	DSL,SARA312,TSCA
0068391-01-5	Alkyl dimethyl benzyl ammonium chloride	Trace	Canada_NPRI,DSL,SARA312,TSCA
0085409-23-0	Alkyl dimethyl ethyl benzyl ammonium chloride (C12-14)	Trace	SARA312
0001336-21-6	AMMONIUM HYDROXIDE	Trace	SARA313, Canada_NPRI,DSL,CERCLA,SARA312,TSCA
0001222-05-5	Cyclopenta[g]-2-benzopyran, 1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethyl-	Trace	DSL,SARA312,TSCA
0000103-95-7	Benzenepropanal, .alpha.-methyl-4-(1-methylethyl)-	Trace	DSL,SARA312,TSCA
0033704-61-9	4H-Inden-4-one, 1,2,3,5,6,7-hexahydro-1,1,2,3,3-pentamethyl-	Trace	DSL,SARA312,TSCA
0000084-66-2	DIETHYL PHTHALATE	Trace	Canada_NPRI,DSL,CERCLA,SARA312,TSCA,RCRA
0054464-57-2	Ethanone, 1-(1,2,3,4,5,6,7,8-octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)-	Trace	DSL,SARA312,TSCA
0000060-12-8	BENZENEETHANOL	Trace	DSL,SARA312,VOC,TSCA
0068391-04-8	Amines, C12-18-alkyldimethyl	Trace	NDSL,SARA312,TSCA
0032388-55-9	Ethanone, 1-[(3R,3aR,7R,8aS)-2,3,4,7,8,8a-hexahydro-3,6,8,8-tetramethyl-1H-3a,7-methanoazulen-5-yl]-	Trace	DSL,SARA312,TSCA
0000081-14-1	Ethanone, 1-[4-(1,1-dimethylethyl)-2,6-dimethyl-3,5-dinitrophenyl]-	Trace	DSL,SARA312,VOC,TSCA
0000140-11-4	BENZYL ACETATE	Trace	DSL,SARA312,VOC,TSCA



**SECTION 16) OTHER INFORMATION****Glossary**

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; N.A. - Not Available; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

**DISCLAIMER**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.