



### Packaging:

20 oz (12 per case) Item No. 1226  
1 Gallon (4 per case) Item No. 1227

### Technical Data:

Appearance: Liquid, Water White  
Odor: Mild  
Shelf Life: > 1 Year  
Flashpoint: >200°F  
pH Value: Neutral  
Non Exempt V.O.C.'s: 280 grams per liter  
Vapor Pressure: 0.8 mm Hg @ 20°C  
Solubility in Water: Partial

#### HMIS HAZARD RATING:

Health: 1 (Slight)  
Flammability: 1 (Moderate)  
Physical Hazard: 0 (Insignificant)  
Personal Protection: B (Gloves & Eye Protection)

Transport Information: Not Regulated in containers  
less than 119 Gallons



WARNING: This product can expose you to chemicals including ethylene glycol and acetaldehyde, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## APPLY Film/Decal Application Fluid

APPLY is an application fluid for vinyl and other film media on hard surface substrates. APPLY will assist in the placement of the graphics, removal of air bubbles, and promote better adhesion. APPLY will also clean the substrate prior to application. Greatly assists in the application of larger graphics. Great for use on cars, glass, signs, metal, and other smooth painted surfaces.

- Cleans substrate
- Floats Film
- Speeds bonding
- Low odor, high flashpoint

### Directions for use:

Clean substrate thoroughly with APPLY and lint free cloth or paper towel. Spray substrate with APPLY, peel off backing and position graphic. Once graphics are perfectly positioned, tape in place (if desired) then squeegee out liquid working from the center outward using a good deal of pressure. Wait a couple of minutes and spray cover tape (if any) with APPLY and remove. Wipe down with clean paper towel.

### Tips:

- When using polyesters, wait 10 minutes
- Test on an inconspicuous area prior to use to insure compatibility
- Can be sprayed directly on adhesive side of decal if desired