



R.S.W. Screen Wash

R.S.W. is a slow evaporative press wash. Great for dried/clogged ink. RSW is the perfect after press run cleanup. Designed for both recirculating systems and manual screen cleaning.

- A low evaporation press wash and recirculating solvent.
- Ideal for quickly washing the screen after the press run.
- Non-toxic, high flash point and pleasant citrus scent.

Packaging:

32 oz (12 per case)	Item No. 4001
1 Gallon (4 per case)	Item No. 4002
5 Gallon Pail	Item No. 4003
55 Gallon Drum	Item No. 4004

Safety:

- Not DOT Regulated for Shipping (as packaged)
- No Hazardous Air Pollutants (HAP's)
- Flashpoint over 141°F
- Low Vapor Pressure
- No Toxic Chemicals
- No California Prop 65 Chemicals.
- No SARA 313 reportable chemicals.
- Neutral pH – Non-Corrosive.

Directions for use:

Card off excess ink. Apply R.S.W. with spray bottle to ink side of screen and wipe-off with absorbent cloth. Repeat on press side of screen.

For a recirculating system, fill tank with R.S.W. and top off as needed. When product loses solvency, clean out system and replace.

Technical Data:

Appearance:	Liquid, Water White
Odor:	Mild Lemon
Shelf Life:	> 1 Year
Flashpoint:	141°F
pH Value:	Neutral
Non Exempt V.O.C.'s:	778.4 grams per liter
Vapor Pressure:	0.8 mm Hg @ 20°C
Solubility in Water:	Partial

HMIS HAZARD RATING:

Health:	1 (Slight)
Flammability:	2 (Moderate)
Physical Hazard:	0 (Insignificant)
Personal Protection:	B (Gloves & Eye Protection)
CA Prop 65 Chemicals:	None
Hazardous Air Pollutants:	None
Transport Information:	Not Regulated in containers less than 119 Gallons

